# **Declaration of Performance**

## **ROARCO Radiator PO-01**

1.Manufacturer:

# ROARCO BVBA RIJKSWEG 15/A 2880 BORNEM/BELGIUM

- 2. Product identification code: Please see attached list in Table A
- 3.Intended use: In heating systems in buildings
- 4. Authorised representative:

N/A

5.System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Construction Products Regulation (EU) 305/2011, Annex V:

## System 3

6.In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 442-1:2014

7. Notified body:

## 1015,SZU

#### 8. Declared Performance:

Reaction to fire: A1

Release of dangerous substances: None Pressure tightness: on leakage at 1,3xMOP

Resistance to pressure

- -No breakage at 1,69XMOP
- -Maximum operating pressure(MOP):600kPa
- -Surface temperature: Maximum 70°C

Rated thermal outputs: See Table A

Thermal output in different operating conditions: See Table A

**Durabilityas:** 

Resistance against corrosion:no corrosion after 100h humidity

Rosistanco against minor impact: Class 0

### 9. Declaration:

The performance of the product identified in point 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 1.

Signed for and on behalf of the manufacturer by:

Name: Celik Arif

Place: Bornem

Date: 29/08/2024

Table A:	Products Covered by DoP No:ROARCO Radiator PO-01			
Product identification code	Rated thermal outputs (Ø30/50/60) W			Thermal output in different operating conditions
PO-1800-500-22-MW-D	827	1589	2006	Ø=10.7254xΔT12777
PO-1800-500-22-MB-D	827	1589	2006	Ø=10.7254xΔT12777
PO-1800-606-26-MW-D	847	1655	2102	Ø=9.7794xΔT1.3116
PO-1800-600-26-MB-D	847	1655	2102	Ø=9.7794xΔT1.3116
PO-1800-600-37-MW-S	629	1197	1507	Ø=8.6273xΔT1.2609
PO-1800-600-37-MB-S	629	1197	1507	Ø=8.6273xΔT1.2609